

Selection Guide of 3-Ph Direct Drive Centrifugal Fans

جدول راهنمای انتخاب فن های سانتریفوژ کوپل مستقیم سه فاز (دوطرفه)

Type	D442	D542	D444	D544	D644	15-13A	15-13B	15-15A	15-15B	مدل
Fan Type	Double Inlet	Double Inlet	Double Inlet	Double Inlet	Double Inlet	Double Inlet	Double Inlet	Double Inlet	Double Inlet	نوع فن
Air Volume [CFM]	3000	3500	3000	3500	4000	4600	5000	5000	6000	هوا دهی [CFM]
Voltage [V]	120~380	120~380	120~380	120~380	120~380	120~380	120~380	120~380	120~380	ولتاژ [V]
Frequency [Hz]	50	50	50	50	50	50	50	50	50	فرکانس [Hz]
Current [A]	2.0	2.2	2.3	2.5	2.7	5.0	5.0	5.5	5.5	جریان مصرفی [A]
Power [W]	750	850	900	950	1050	1900	1900	2100	2100	توان مصرفی [W]
Speed [rpm]	850	850	700	700	700	700	700	700	700	سرعت [rpm]
Insulation Class	H	H	H	H	H	H	H	H	H	کلاس عایقی
Protection Class	IP65	IP65	IP65	IP65	IP65	IP65	IP65	IP65	IP65	کلاس حفاظتی
Starting Current	5	5	5	5	5	10	10	10	10	جریان راه اندازی [A]
Min/Max Air Temp.	- 40° +60°	- 40° +60°	- 40° +60°	- 40° +60°	- 40° +60°	- 40° +60°	- 40° +60°	- 40° +60°	- 40° +60°	درجه حرارت [°C]
Dimentions H*W*D	54* 30*50	59* 30*54	54* 40*50	59* 40*54	62* 40*57	62* 42*56	64* 42*58	62* 47*56	64* 47*58	ابعاد فن [Cm]
Outlet Area H*W	36*30	36*30	36*40	36*40	40*40	42*42	42*42	42*47	42*47	دهانه خروجی [Cm]
Blade Type	Forward Curved	Forward Curved	Forward Curved	Forward Curved	Forward Curved	Forward Curved	Forward Curved	Forward Curved	Forward Curved	نوع پره
Net Weight [Kg]	22	24	28	30	32	52	52	54	54	وزن خالص [Kg]